

# **= Newhouse =**

**Mfg. Co. Inc. - Redmond, OR**

**HEAVY DUTY  
ONION FLAIL SHREDDERS  
12.9, 15 & 17.5FT MODELS**



**HIGH PROFILE BODY THAT ALLOWS BETTER BROADCASTING OF  
MATERIAL  
280HP GEARBOX AND YOUR CHOICE OF CHAIN OR CHAIN AND BELT  
FOR THE FRONT DEFLECTORS.**

**NEWHOUSE MANUFACTURING COMPANY INC.  
1048 N. SIXTH STREET, REDMOND OR 97756  
PHONE: (541) 548-1055 FAX: (541) 548-4144  
WEB SITE: [www.newhouse-mfg.com](http://www.newhouse-mfg.com)  
E-mail: [info@newhouse-mfg.com](mailto:info@newhouse-mfg.com)  
1-800-587-1055**

**DEALER**

**Tough Steel Construction** : Every part is built to withstand years of hard work. The Shredder hood is constructed of wear resistant steel that has a higher abrasion resistance than AR200 wear plate, rotor is constructed of 10-3/4" O.D. X 1/2" wall with 2-3/16" alloy shafting. **ALL ROTORS ARE COMPUTER BALANCED TO ASSURE SMOOTH OPERATION.**



**BELT DRIVEN POWER TRAIN**  
5VX COGGED BELTS, THESE BELTS HAVE A HIGHER HP RATING THAN THE OLD "C" SECTION BELTS.



**Cupped Knife** - The vacuum created by the standard 5/16" thick X 2" wide cupped knives lifts the flattened material into the rotor for a complete and uniform cut.

**Contoured Rotor** - By using a combination of 5", 6-1/2", 8", and 9-1/2" long flails we are able to offer contoured flail patterns to meet virtually any row

Large opening in the back to allow excellent broadcasting of the material.



### SPECIFICATIONS

MODEL	O1230	O1530	O1753
OVER ALL WIDTH	168"	192"	229"
CUTTING WIDTH	155"	180"	210"
CUTTING HEIGHT	4" TO 12"	4" TO 12"	4" TO 12"
PTO RPM	1000	1000	1000
APPROX O/A HEIGHT W/O JACKS & DEPTH WHEELS	48"	48"	48"
DEPTH W/O DEPTH WHEELS & 3-POINT HITCH	60"	60"	60"
NUMBER OF FLAILS	84	102	124
NUMBER OF WHEELS (Min. recommended)	2	2	3
GEAR BOX RATING	280 HP	280 HP	280 HP
APPROX. WEIGHT	4200 LBS	4600 LBS	5000 LBS
NUMBER OF DRIVE BELTS	4	4/6	8



**Heavy Duty**  
**2-3/16"**  
**Alloy Shafting**