

= Newhouse =

Mfg. Co. Inc. - Redmond, OR

HEAVY DUTY UNIVERSAL FLAIL SHREDDER 15FT THROUGH 24FT MODELS



FRONT VIEW OF SHREDDER SHOWING REAR DOORS OPEN



**REAR VIEW OF SHREDDER SHOWING REAR DOORS OPEN.
THIS ALLOWS HIGH VOLUME BROADCAST SHREDDING!
CLOSE THE DOORS FOR TRADITIONAL SHREDDING**

**NEWHOUSE MANUFACTURING COMPANY INC.
1048 N. SIXTH STREET, REDMOND OR 97756
PHONE: (541) 548-1055 FAX: (541) 548-4144
WEB SITE: www.newhouse-mfg.com
E-mail: info@newhouse-mfg.com
1-800-587-1055**

DEALER

ALLOY HOOD CONSTRUCTION! The body and rear doors are made from alloy steel to give more than double the strength of mild steel and a higher wear resistance than AR200 wear plate!



BELT DRIVEN POWER TRAIN
6 groove sheaves are standard on all models. Heavy duty spring loaded belt tensioners assure proper tension at all times.



Center drum bearings
are QM / Timken
heavy duty dual
spherical bearings



Rear doors have been added to the back. This allows you to run with the doors closed for a very fine chop or open for a high volume coarser broadcast chop. This picture shows the third position which is fully open, this allows for unprecedented access to the drums and bearings for easy maintenance and flail replacement!



DEBRIS DEFLECTOR SYSTEM!

You can choose from chain only or chain and belt together depending on your particular field conditions.



280HP GEARBOX WITH BUILT IN OVERRUNNING CLUTCH.
This clutch design offers significant life improvement over a typical external clutch



Finger grates are standard on all machines and are made from AR400 wear plate for exceptional long life, these grates allow for a fine chop, but also allow the machine to be less prone to plugging.



Completely redesigned rear tire arm mounting system. This system uses greaseless composite bushings for the tubes to pivot on

SPECIFICATIONS

MODEL	U1530	U1830	U2030	U2230	U2440
OVERALL WIDTH	207"	243"	267"	292.5"	316.5"
CUTTING WIDTH	180"	216"	239.5"	265"	289"
PTO RPM	1000	1000	1000	1000	1000
APPROX O/A HEIGHT W/O JACKS & WHEELS	39"	39"	39"	39"	39"
DEPTH W/O DEPTH WHEELS & HITCH	64"	64"	64"	64"	64"
TOTAL NUMBER OF BELTS	12	12	12	12	12
FLAIL TIP SPEED FPM/MPH AT 1949RPM	14,006/159	14,006/159	14,006/159	14,006/159	14,006/159
GEAR BOX RATING	280HP	280 HP	280 HP	280 HP	280 HP
FLAIL ROTOR RPM	1680/2000	1680/2000	1680/2000	1680/2000	1680/2000
NUMBER OF FLAILS	176	208	224	240	256