

= Newhouse =

Mfg. Co. Inc. - Redmond, OR

**HEAVY DUTY
WINDROWING FLAIL SHREDDERS
15ft MODEL**



THE HEAVYWEIGHT OF FLAIL SHREDDERS JUST STEPPED INTO THE MIX!

**NEWHOUSE MANUFACTURING COMPANY INC.
1048 N. SIXTH STREET, REDMOND OR 97756
PHONE: (541) 548-1055 FAX: (541) 548-4144
WEB SITE: www.newhouse-mfg.com
E-mail: info@newhouse-mfg.com
1-800-587-1055**

DEALER

Tough Steel Construction : Every part is built to withstand years of hard work. The Shredder hood is constructed of a one piece 1/4" steel plate. The rotor is 10-3/4" O.D. X 1/2" wall with 2-3/16" alloy shafting and triple seal bearings. **ALL ROTORS ARE COMPUTER BALANCED TO ASSURE SMOOTH OPERATION.**



Back hood can open fully to allow material to be spread out over the field for a more conventional shredding style.

Large opening for high speed windrowing



NEW FOR 2013! All cross conveyors are now made with steel pintle chain and a high grade replaceable composite floor



This shows a field before and after windrowing. This corn was on 22" centers. We were using a 135hp tractor. The windrows were between 4 and 5ft wide and roughly 26" tall.



A cushion style check valve insures long trouble free life on all hydraulic components


SPECIFICATIONS

MODEL	C1535
OVERALL WIDTH	204"
CUTTING WIDTH	180"
PTO RPM	1000
APPROX O/A HEIGHT W/O JACKS & WHEELS	48-1/2"
DEPTH W/O DEPTH WHEELS & HITCH	98"
TOTAL NUMBER OF BELTS	6
FLAIL TIP SPEED FPM/MPH	10,812/123
GEAR BOX RATING	280HP
FLAIL ROTOR RPM	1400
NUMBER OF FLAILS	102

Specifications subject to change without notice



Massive belt drive system. One of the strongest in the industry.



We use a heavy duty 280hp gearbox with built in overrunning clutch to assure the highest reliability.